



# X1p

DMR hand-held radio

The X1p is an ultra-thin digital hand-held radio with a full power key pad, which is developed in compliance with the ETSI DMR standard.



# Radio

## X1p

DMR hand-held radio



### Highlights

#### Advanced encryption

The AES encryption algorithm and the 40 to 256 bit digit encryption keys ensure secure communication.

#### Supports Hytera Bluetooth earpieces\*

The X1p supports Bluetooth earpieces from Hytera, facilitating operations including PTT.

#### Open USB interface

An open USB port facilitates secondary and application development.

#### GPS positioning

The built-in GPS module supports GIS applications (geographic information system).

#### Dual mode (analog & digital)

By supporting analog and digital operation, the X1p ensures a smooth migration from analog to digital.

#### Versatile voice calls

Versatile voice calls include individual call, group call and all-call.

#### Direct mode

Like the other DMR terminals from Hytera, the X1p supports the use of both timeslots in direct mode. In direct mode two calls can be held in the same area at the same time.

#### Rich signalling

Supports multiple advanced analog signalling techniques, including HDC1200, DTMF, 2-tone\* and 5-tone, providing more expansion capacity.

#### Software upgradable

Upgradable software enables new features. By changing the firmware software the radio can be used for DMR Tier II or DMR Tier III without buying a new radio.



This radio is a perfect combination of structural rigidity, versatile features and refined design; secure communication ensured by AES encryption algorithm & 256 digit dynamic encryption keys; convenient application development facilitated by a built-in Bluetooth and USB

port; and worry-free handling achieved by IP67 protection. All comes with a surprisingly small size: 21 mm thin when using a 1100 mAh Li-ion battery.

## Innovative Design

### Multiple languages

The user interface of the X1p supports different languages allowing users to select it per their needs. T9 support for text input is available.

### Large-size colour display

X1p adopts a 1.8" TFT LCD display (65,536 colours), allowing good visibility even under outdoor light conditions.

### Key pad

The key pad can be deactivated automatically. For enabling the key pad a password can be set.



### Extra operation time

Compared with an analog radio, the X1p can obtain an extra operation time of 40% by using DMR TDMA. This means an operation time up to 10 hours.

### IP67 compliance

Complies with IP67 requirements, withstanding up to 1 m submersion in water for at least 30 minutes.

### Rugged & reliable

Complies with MIL-STD-810 C/D/E/F/G standards and passes HALT (Highly Accelerated Life Test).

The features marked with \* are available in future versions of the X1p.

## Versatile accessories for specific tasks (excerpt)

Li-Ion battery (1800mAh) BL1809	3-wire surveillance earpiece with acoustic tube EAN21	Remote swivel earset EHN20	Remote earbud ESN14	Remote C-earset EHN21	Vest NCN009
Digital wireless covert earpiece (flatpack sensor) EWN08	Belt charger CH04L01	MCU dual-pocket charger CH10L15	Belt clip PCN005		

The illustrations shown above are only for reference purposes. The products themselves may vary from these representations.

## Technical Data

General data	
Frequency range	VHF: 136 MHz – 174 MHz UHF1: 400 MHz – 470 MHz UHF2: 450 MHz – 520 MHz UHF3: 350 MHz – 400 MHz
Channel capacity	1024
Zone capacity	64
Channel spacing	12.5 / 20 / 25 kHz
Operating voltage	7.4 V
Battery	1100 mAh (Li-ion battery, included in scope of delivery) 1800 mAh (Li-ion battery)
Battery life (5-5-90 duty cycle, high TX power)	<b>analog:</b> over 8 hours (1800 mAh Li-ion battery) <b>digital:</b> over 10 Hours (1800 mAh Li-ion battery)
Frequency stability	± 1.5 ppm
Antenna impedance	50 Ω
Dimensions (L×W×H) (without antenna)	119,5 × 57 × 21 mm (1100 mAh Li-ion battery) 119,5 × 57 × 26 mm (1800 mAh Li-ion battery)
Weight	about 240 g (1100 mAh Li-ion battery) about 280 g (1800 mAh Li-ion battery)
LCD display	160 × 128 pixels, 65536 colors 1.8 inch, 4 rows

Transmitter	
Sensitivity analog	0.3 μV (12 dB SINAD) 0.22 μV (Typical) (12 dB SINAD) 0.4 μV (20 dB SINAD)
Sensitivity digital	0.3 μV / BER 5%
<b>Selectivity</b> TIA-603 ETSI	60 dB at 12.5 kHz / 70 dB at 20 / 25 kHz 60 dB at 12.5 kHz / 70 dB at 20 / 25 kHz
<b>Intermodulation</b> TIA-603 ETSI	70 dB at 12.5 / 20 / 25 kHz 65 dB at 12.5 / 20 / 25 kHz
<b>Spurious response rejection</b> TIA-603 ETSI	70 dB at 12.5 / 20 / 25 kHz 70 dB at 12.5 / 20 / 25 kHz
Hum and noise (S/N)	40 dB at 12.5 kHz 43 dB at 20 kHz 45 dB at 25 kHz
Rated audio distortion	≤ 3 %
Audio response	+ 1 dB ~ - 3 dB
Conducted spurious emission	< - 57 dBm

Your Hytera partner:



### Hytera Mobilfunk GmbH

**Address:** Fritz-Hahne-Straße 7, 31848 Bad Münder, Germany  
**Phone:** +49 (0)5042 / 998-0 **Fax:** +49 (0)5042 / 998-105 **E-Mail:** info@hytera.de  
[www.hytera.de/en](http://www.hytera.de/en)

Receiver	
RF power output	VHF max. high power: 5 W UHF1/UHF3 max. high power: 4 W
FM modulation	11 KΦF3E at 12.5 kHz 14 KΦF3E at 20 kHz 16 KΦF3E at 25 kHz
4FSK digital modulation	12.5 kHz data only: 7K60FXD 12.5 kHz data & voice: 7K60FXW
Conducted/Radiated Emission	-36 dBm < 1 GHz -30 dBm > 1 GHz
Modulation limiting	± 2.5 kHz at 12.5 kHz ± 4.0 kHz at 20 kHz ± 5.0 kHz at 25 kHz
FM hum & noise	40 dB at 12.5 kHz 43 dB at 20 kHz 45 dB at 25 kHz
Adjacent Channel Power	60 dB at 12.5 kHz 70 dB at 20/25 kHz
Audio Response	+ 1 dB ~ - 3 dB
Audio Distortion	≤ 3 %
Digital Vocoder Type	AMBE++ (for Europe)
Digital Protocol	ETSI-TS102 361-1, 2 & 3

Ambient data	
Operating temperature range	- 30 °C ~ + 60 °C
Storage temperature range	- 40 °C ~ + 85 °C
ESD	IEC 61000-4-2 (level 4) ± 8 kV (contact), ± 15 kV (air)
American military standard	MIL-STD-810 C/D/E/F/G
Dust & Water Intrusion	IP67 Standard
Humidity	Per MIL-STD-810 C/D/E/F/G Standard
Shock & vibration	Per MIL-STD-810 C/D/E/F/G Standard

GPS	
TTFF (Time To First Fix) cold start	< 1 minute
TTFF (Time To First Fix) hot start	< 10 seconds
Horizontal accuracy	< 10 meters

All specifications are subject to change without notice due to continuous development.

For more information visit: [www.hytera.de/en](http://www.hytera.de/en)

Contact us when you are interested in buying Hytera products, sales partnership or application partnership: ✉ [info@hytera.de](mailto:info@hytera.de)



SGS Certificate DE11/81829313

Hytera Mobilfunk GmbH reserves the right to alter product design and to change the specification. If a printing error occurs, Hytera Mobilfunk GmbH assumes no liability. All specifications subject to change without notice.

Encryption features are optional and require a separate configuration, subject to German and European export regulations.

**HYT** Hytera are registered trademarks of Hytera Co. Ltd. ACCESSNET® and all derivatives are protected trademarks of Hytera Mobilfunk GmbH. 2012 Hytera Mobilfunk GmbH. All rights reserved.